

Description

length: 0.74", grip: 0.375", thread: 10-32, flush head, close tolerance, aluminum coated corrosion resistant steel, philips recess

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS7203A6
Minimum Qty (MOQ):	10
NSN:	5305-01-267-9917
ECCN:	EAR99



* See page 2 for technical characteristics

P/N NAS7203A6 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.365 Inches Nominal
Fastener Length:	0.725 Inches Minimum And 0.755 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.338 Inches Minimum And 0.381 Inches Maximum
Grip Diameter:	0.1879 Inches Minimum And 0.1887 Inches Maximum
Internal Drive Style:	Cross Recess Type li
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.365 Inches Minimum And 0.385 Inches Maximum
Thread Quantity Per Inch:	32
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 11,cl 2 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS7203A6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.