

Description

Thread: 10-32, Thread Length: 11/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS7203U6
Minimum Qty (MOQ):	15 EA
NSN:	5306-01-589-7715
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS7203U6 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.181 Inches Minimum And 0.184 Inches Maximum
Fastener Length:	0.725 Inches Minimum And 0.755 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.338 Inches Minimum And 0.381 Inches Maximum
Grip Diameter:	0.189 Inches Minimum And 0.190 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.365 Inches Minimum And 0.385 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Part Name Assigned By Controlling Agency:	Bolt 100 Degrees Head, Cruciform Recess, Close Tolerance, A286 Cres, Long Thread, Self-locking And Nonlocking
Material:	Iron Alloy 660 Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS7203U6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.