

Description

Fastener Length: 1-5/16", Thread: 1/4-28, Thread Length: 27/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | NAS7204U14 |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5306-01-369-8197 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |



* See page 2 for technical characteristics

P/N NAS7204U14 Specifications

| | |
|--|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.425 Inches Nominal |
| Fastener Length: | 1.285 Inches Minimum And 1.315 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.508 Inches Nominal |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 0.865 Inches Minimum And 0.885 Inches Maximum |
| Thread Quantity Per Inch: | 28 |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams5731 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas7204u14 Professional/industrial Association Standard |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS7204U14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.