

**Description**

Fastener Length: 35/64", Thread: 1/4-28, Thread Length: 27/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                               |
|-------------------------|-------------------------------|
| SKU / Model:            | NAS7204U2                     |
| Minimum Qty (MOQ):      | 5 EA                          |
| NSN:                    | 5305-01-524-1551              |
| Schedule B:             | 7318.15.8085                  |
| ECCN:                   | EAR99                         |
| National Motor Freight: | 096640, Screws, Iron Or Steel |

NO IMAGE  
AVAILABLE

## P/N NAS7204U2 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Thread Length:</b>                                 | 0.425 Inches Nominal   |
| <b>Fastener Length:</b>                               | 0.550 Inches Nominal   |
| <b>Head Style:</b>                                    | Flat Countersunk   |
| <b>Head Diameter:</b>                                 | 0.508 Inches Nominal   |
| <b>Grip Diameter:</b>                                 | 0.625 Inches Nominal   |
| <b>Internal Drive Style:</b>                          | Cross Recess Type 1  |
| <b>Nominal Thread Diameter:</b>                       | 0.250 Inches   |
| <b>Grip Length:</b>                                   | 0.125 Inches Nominal   |
| <b>Thread Quantity Per Inch:</b>                      | 28   |
| <b>Minimum Tensile Strength:</b>                      | 160000 Pounds Per Square Inch  |
| <b>Countersink Angle:</b>                             | 99.0 Degrees Minimum And 101.0 Degrees Maximum   |
| <b>Material:</b>                                      | Steel Corrosion Resisting Overall  |
| <b>Material Document And Classification:</b>          | Ams5731 Assn Std 1st Material Response Overall Or Ams5737 Assn Std 2nd Material Response Overall |
| <b>Surface Treatment:</b>                             | Passivate Overall  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response Overall   |
| <b>Thread Series Designator:</b>                      | Unjf   |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS7204U2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.