

Description


for instrument use

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS722CK80080
Minimum Qty (MOQ):	5
NSN:	5305-01-236-7556
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS722CK80-080 Specifications

Thread Direction:	Right-hand
Thread Length:	0.056 Inches Minimum And 0.080 Inches Maximum
Fastener Length:	0.072 Inches Minimum And 0.080 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.058 Inches Minimum And 0.062 Inches Maximum
Head Height:	0.021 Inches Minimum And 0.025 Inches Maximum
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.0315 Inches
Nonstandard Thread Pitch Diameter:	+0.0254/+0.0264 Inches
Thread Quantity Per Inch:	127
Hardness Rating:	28.0 Rockwell C Minimum Overall And 34.0 Rockwell C Maximum Overall
Material:	Steel Comp 416 Overall
Material Document And Classification:	Qq-s-763 Fed Spec Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unm
Specification/standard Data:	80205-nas722 Professional/industrial Association Standard

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS722CK80-080> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.