

Description

Fastener Length: 7/64", Thread: 1-3/8-, Thread Length: 3/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS723B140120P
Minimum Qty (MOQ):	15 EA
NSN:	5305-01-180-9101
Schedule B:	7415.39.0000
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS723B140-120P Specifications

Thread Direction:	Right-hand
Thread Length:	0.028 Inches Minimum And 0.098 Inches Maximum
Fastener Length:	0.110 Inches Minimum And 0.120 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.097 Inches Minimum And 0.103 Inches Maximum
Internal Drive Style:	Slot
Nominal Thread Diameter:	1.4 Millimeters
Thread Pitch In Millimeters:	0.3
Countersink Angle:	98.0 Degrees Minimum And 102.0 Degrees Maximum
Material:	Copper Alloy 360 Overall
Material Document And Classification:	Qq-b-626,comp 22 Fed Spec Single Material Response Overall
Thread Series Designator:	Unm
Specification/standard Data:	80205-nas723 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS723B140-120P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.