

Description

NAS73-4-008 Sleeve Bushing

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | NAS734008 |
| Minimum Qty (MOQ): | 1 |
| NSN: | 3120-00-287-9729 |
| ECCN: | EAR99 |
| National Motor Freight: | 114850, Bearing / Bushing O / T Ball / Roller I / S |



NO IMAGE
AVAILABLE

P/N NAS73-4-008 Specifications

| | |
|---|--|
| Overall Length: | 0.5050 Inches Minimum And 0.5100 Inches Maximum |
| Body Outside Diameter: | 0.4351 Inches Minimum And 0.4361 Inches Maximum |
| Body Inside Diameter: | 0.2495 Inches Minimum And 0.2510 Inches Maximum |
| Lubricant Accommodation Style: | Grooved Circular |
| Corner Shape: | Chamfered Inside Right Corner |
| Corner Shape: | Chamfered Inside Left Corner |
| Corner Shape: | Square Outside Left Corner |
| Corner Shape: | Square Outside Right Corner |
| Surface Groove Location And Quantity: | 1 External |
| Material: | Steel Comp 8630 Overall Or Steel Comp 4130 Overall |
| Material Document And Classification: | Mil-s-6050 Mil Spec 1st Material Response Overall Or Mil-s-6758 Mil Spec 2nd Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall |
| Style Designator: | 17c Solid, Plain, No Outside Flanges |
| Style Designator: | Solid, Plain, No Outside Flanges |
| Specification/standard Data: | 80205-nas73 Professional/industrial Association Standard |

How to Order

Order this sleeve bushing from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS73-4-008> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.