



Military-Fasteners.com

P/N NAS7303A2

Description

Fastener Length: 1/2", Thread: 10-32, Thread Length: 23/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS7303A2
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-434-5921
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS7303A2 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.365 Inches Nominal
Fastener Length:	0.475 Inches Minimum And 0.505 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.338 Inches Minimum And 0.381 Inches Maximum
Grip Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.1900 Inches
Grip Length:	0.110 Inches Minimum And 0.140 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 Assn Std Single Material Response Overall
Surface Treatment:	Aluminum Overall
Surface Treatment Document And Classification:	Nas4006 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas7303 Professional/Industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS7303A2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.