



Military-Fasteners.com

P/N NAS7303A9

Description

Fastener Length: 15/16", Thread: 10-32, Thread Length: 23/64", NAS7303 series bolt

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

|                         |                                      |
|-------------------------|--------------------------------------|
| SKU / Model:            | NAS7303A9                            |
| Minimum Qty (MOQ):      | 1                                    |
| NSN:                    | 5305-01-338-4030                     |
| Schedule B:             | 8108.90.3060                         |
| ECCN:                   | 9A991                                |
| National Motor Freight: | 136500, Metal Noi / Metal Alloys Noi |



\* See page 2 for technical characteristics

## P/N NAS7303A9 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Thread Length:</b>                                 | 0.365 Inches Nominal   |
| <b>Fastener Length:</b>                               | 0.913 Inches Minimum And 0.943 Inches Maximum  |
| <b>Head Style:</b>                                    | Flat Countersunk   |
| <b>Head Diameter:</b>                                 | 0.338 Inches Minimum And 0.381 Inches Maximum  |
| <b>Grip Diameter:</b>                                 | 0.1885 Inches Minimum And 0.1895 Inches Maximum  |
| <b>Internal Drive Style:</b>                          | Cross Recess Type 1  |
| <b>Nominal Thread Diameter:</b>                       | 0.190 Inches   |
| <b>Grip Length:</b>                                   | 0.552 Inches Minimum And 0.572 Inches Maximum  |
| <b>Thread Quantity Per Inch:</b>                      | 32   |
| <b>Minimum Tensile Strength:</b>                      | 160000 Pounds Per Square Inch  |
| <b>Countersink Angle:</b>                             | 99.0 Degrees Minimum And 101.0 Degrees Maximum   |
| <b>Material:</b>                                      | Titanium Alloy Uns R56400 Overall  |
| <b>Material Document And Classification:</b>          | Ams4928 Assn Std Single Material Response Overall Or Ams4967 Assn Std Single Material Response Overall |
| <b>Surface Treatment:</b>                             | Aluminum Overall   |
| <b>Surface Treatment Document And Classification:</b> | Nas4006 Assn Std Single Treatment Response Overall   |
| <b>Thread Series Designator:</b>                      | Unjf   |
| <b>Specification/standard Data:</b>                   | 80205-nas7303 Professional/Industrial Association Standard   |

## How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS7303A9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.