

P/N NAS7303U5

Military-Fasteners.com

Description

Fastener Length: 43/64", Thread: 10-32, Thread Length: 3/8

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	NAS7303U5
Minimum Qty (MOQ):	10
NSN:	5305-01-627-1661
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel



P/N NAS7303U5 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.365 Inches Nominal
Fastener Length:	0.663 Inches Minimum And 0.693 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.338 Inches Minimum And 0.381 Inches Maximum
Grip Diameter:	0.188 Inches Minimum And 0.189 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
lii End Item Identification:	B-1
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.302 Inches Minimum And 0.322 Inches Maximum
Thread Quantity Per Inch:	32
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
lii Part Name Assigned By Controlling Agency:	Bolt Close Tolerance
Material:	Titanium Alloy Uns R56400 Overall
Thread Series Designator:	Unjf

How to Order

Order this close tolerance screw from our inventory online by visiting <u>https://military-fasteners.com/screws/close+tolerance+screws/NAS7303U5</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.