

Description

Fastener Length: 43/64", Thread: 10-32, Thread Length: 3/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-------------------------------|
| SKU / Model: | NAS7303U5 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5305-01-627-1661 |
| ECCN: | EAR99 |
| National Motor Freight: | 096640, Screws, Iron Or Steel |

NO IMAGE
AVAILABLE

P/N NAS7303U5 Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.365 Inches Nominal |
| Fastener Length: | 0.663 Inches Minimum And 0.693 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.338 Inches Minimum And 0.381 Inches Maximum |
| Grip Diameter: | 0.188 Inches Minimum And 0.189 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| iii End Item Identification: | B-1 |
| Nominal Thread Diameter: | 0.190 Inches |
| Grip Length: | 0.302 Inches Minimum And 0.322 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| iii Part Name Assigned By Controlling Agency: | Bolt Close Tolerance |
| Material: | Titanium Alloy Uns R56400 Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS7303U5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.