

Description

Fastener Length: 1-41/64", Thread: 7/16-20, Thread Length: 11/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS7307A15Y
Minimum Qty (MOQ):	45 EA
NSN:	5306-01-607-7606
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS7307A15Y Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.6940 Inches Nominal
Fastener Length:	1.6170 Inches Minimum And 1.6470 Inches Maximum
Head Style:	Fillister Countersunk
Head Diameter:	0.810 Inches Minimum And 0.889 Inches Maximum
Head Height:	0.028 Inches Maximum
Grip Diameter:	0.4365 Inches Minimum And 0.4370 Inches Maximum
End Item Identification:	Kc-135 Acft
Nominal Thread Diameter:	0.4375 Inches
Grip Length:	0.928 Inches Minimum And 0.948 Inches Maximum
Thread Quantity Per Inch:	20
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Part Name Assigned By Controlling Agency:	Bolt, 100 Deg Head, Cruciform Recess Close Tolerance
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams4928 Assn Std Single Material Response Or Ams4967 Assn Std Single Material Response Overall
Surface Treatment:	Aluminum Overall
Surface Treatment Document And Classification:	Nas4006 National Std/spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS7307A15Y> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.