

**Description**

Fastener Length: 17/32", Thread: 6-32, Thread Length: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                               |
|-------------------------|-------------------------------|
| SKU / Model:            | NAS74014                      |
| Minimum Qty (MOQ):      | 20 EA                         |
| NSN:                    | 5305-01-338-0919              |
| Schedule B:             | 7318.15.8085                  |
| ECCN:                   | 9A991                         |
| National Motor Freight: | 096640, Screws, Iron Or Steel |

NO IMAGE  
AVAILABLE

## P/N NAS7401-4 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Thread Length:</b>                                 | 0.276 Inches Nominal  |
| <b>Fastener Length:</b>                               | 0.511 Inches Minimum And 0.541 Inches Maximum               |
| <b>Head Style:</b>                                    | Flat Countersunk  |
| <b>Head Diameter:</b>                                 | 0.246 Inches Minimum And 0.280 Inches Maximum               |
| <b>Grip Diameter:</b>                                 | 0.1365 Inches Minimum And 0.1375 Inches Maximum             |
| <b>Internal Drive Style:</b>                          | Cross Recess Type 1   |
| <b>Nominal Thread Diameter:</b>                       | 0.138 Inches  |
| <b>Grip Length:</b>                                   | 0.240 Inches Minimum And 0.260 Inches Maximum               |
| <b>Thread Quantity Per Inch:</b>                      | 32  |
| <b>Minimum Tensile Strength:</b>                      | 160000 Pounds Per Square Inch                               |
| <b>Countersink Angle:</b>                             | 99.0 Degrees Minimum And 101.0 Degrees Maximum              |
| <b>Part Name Assigned By Controlling Agency:</b>      | Navy Special Project  |
| <b>Material:</b>                                      | Steel Comp E4340 Overall Or Steel Comp 8740 Overall         |
| <b>Surface Treatment:</b>                             | Cadmium Overall And Chromate Overall                        |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,ty2,cl2 Fed Spec Single Treatment Response Overall |
| <b>Thread Series Designator:</b>                      | Unjf  |
| <b>Specification/standard Data:</b>                   | 80205-nas7401 Professional/Industrial Association Standard  |

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS7401-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.