

**Description**

length: 1.135", grip: 0.812", thread: 10-32, 100°, flush head close tolerance bolt - corrosion resistant steel - philips recess"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS740313
Minimum Qty (MOQ):	100
NSN:	5306-01-301-7645



## P/N NAS7403-13 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.318 Inches Minimum And 0.328 Inches Maximum
<b>Fastener Length:</b>	1.121 Inches Minimum And 1.151 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.338 Inches Minimum And 0.381 Inches Maximum
<b>Grip Diameter:</b>	0.1885 Inches Minimum And 0.1895 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Grip Length:</b>	0.803 Inches Minimum And 0.823 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Material:</b>	Steel Comp 4340 Overall Or Steel Comp 8740 Overall
<b>Material Document And Classification:</b>	Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 3rd Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS7403-13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.