

Description

length: 1.323", grip: 1", thread: 10-32, 100°, flush head close tolerance bolt - corrosion resistant steel - philips recess"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS740316
Minimum Qty (MOQ):	100
NSN:	5306-01-322-1595



* See page 2 for technical characteristics

P/N NAS7403-16 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.318 Inches Minimum And 0.328 Inches Maximum
Fastener Length:	1.308 Inches Minimum And 1.338 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.338 Inches Minimum And 0.381 Inches Maximum
Grip Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.990 Inches Minimum And 1.010 Inches Maximum
Thread Quantity Per Inch:	32
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Comp 4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 3rd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS7403-16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.