

Description

length: 0.448", grip: 0.125", thread: 10-32, flush head close tolerance bolt, corrosion resistant steel, philips recess

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS74032
Minimum Qty (MOQ):	100
NSN:	5306-01-499-1965
ECCN:	EAR99



P/N NAS7403-2 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.284 Inches Minimum And 0.362 Inches Maximum
Fastener Length:	0.433 Inches Minimum And 0.463 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.381 Inches Maximum
Grip Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Point Diameter:	0.181 Inches Minimum And 0.184 Inches Maximum
Point Style:	Flat
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.084 Inches Minimum And 0.159 Inches Maximum
Thread Quantity Per Inch:	32
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Aluminum Alloy Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416, Type II, Class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS7403-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.