

**Description**

length: 0.448", grip: 0.125", thread: 10-32, flush head close tolerance bolt, corrosion resistant steel, philips recess

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS74032
Minimum Qty (MOQ):	100
NSN:	5306-01-499-1965
ECCN:	EAR99



## P/N NAS7403-2 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.284 Inches Minimum And 0.362 Inches Maximum
<b>Fastener Length:</b>	0.433 Inches Minimum And 0.463 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.381 Inches Maximum
<b>Grip Diameter:</b>	0.1885 Inches Minimum And 0.1895 Inches Maximum
<b>Point Diameter:</b>	0.181 Inches Minimum And 0.184 Inches Maximum
<b>Point Style:</b>	Flat
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Grip Length:</b>	0.084 Inches Minimum And 0.159 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Material:</b>	Aluminum Alloy Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416, Type II, Class 2 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS7403-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.