

Description

length: 0.511", grip: 0.188", thread: 10-32, flush head close tolerance bolt, corrosion resistant steel, philips recess

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS74033
Minimum Qty (MOQ):	100
NSN:	5306-01-269-6886
ECCN:	EAR99



* See page 2 for technical characteristics

P/N NAS7403-3 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.318 Inches Minimum And 0.328 Inches Maximum
Fastener Length:	0.496 Inches Minimum And 0.526 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.338 Inches Minimum And 0.381 Inches Maximum
Grip Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.178 Inches Minimum And 0.198 Inches Maximum
Thread Quantity Per Inch:	32
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Comp 4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 3rd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty2cl2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS7403-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.