

Description

Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | NAS7510009 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 3120-01-256-9768 |
| National Motor Freight: | 114820, Bearings / Bushings Noi Ball / Roller |

NO IMAGE
AVAILABLE

P/N NAS75-10-009 Specifications

| | |
|---|--|
| Overall Length: | 0.2762 Inches Minimum And 0.2812 Inches Maximum |
| Body Outside Diameter: | 0.8132 Inches Minimum And 0.8142 Inches Maximum |
| Body Inside Diameter: | 0.6250 Inches Minimum And 0.6265 Inches Maximum |
| Corner Shape: | Chamfered Inside Right Corner |
| Corner Shape: | Chamfered Inside Left Corner |
| Corner Shape: | Square Outside Left Corner |
| Corner Shape: | Square Outside Right Corner |
| Material: | Steel Comp 4130 Overall Or Steel Comp 8630 Overall |
| Material Document And Classification: | Mil-s-6758 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall |
| Style Designator: | 17c Solid, Plain, No Outside Flanges |
| Specification/standard Data: | 80205-nas75 Professional/industrial Association Standard |

How to Order

Order this bushing from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS75-10-009> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.