

Description

Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS7510014
Minimum Qty (MOQ):	10 EA
NSN:	3120-00-917-7430
National Motor Freight:	114850, Bearing / Bushing O / T Ball / Roller I / S



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS75-10-014 Specifications

Overall Length:	0.4325 Inches Minimum And 0.4375 Inches Maximum
Body Outside Diameter:	0.8132 Inches Minimum And 0.8142 Inches Maximum
Body Inside Diameter:	0.6250 Inches Minimum And 0.6265 Inches Maximum
Corner Shape:	Chamfered Inside Right Corner
Corner Shape:	Chamfered Inside Left Corner
Corner Shape:	Square Outside Left Corner
Corner Shape:	Square Outside Right Corner
Surface Finish:	125.0 Microinches Intermediate Layer
Special Features:	Id And Od To Be Parallel And Concentric Within 0.0030 Tir
Material:	Steel Comp 4130 Overall Or Steel Comp 8630 Overall
Material Document And Classification:	Mil-s-6758 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Style Designator:	17c Solid, Plain, No Outside Flanges
Specification/standard Data:	80205-nas75 Professional/industrial Association Standard

How to Order

Order this bushing from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS75-10-014> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.