

**Description**

Length: 15/32"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS7510015
Minimum Qty (MOQ):	5 EA
NSN:	3120-00-720-2359
National Motor Freight:	115620, Bushings Noi I / S

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS75-10-015 Specifications

<b>Overall Length:</b>	0.4640 Inches Minimum And 0.4690 Inches Maximum
<b>Body Outside Diameter:</b>	0.8132 Inches Minimum And 0.8142 Inches Maximum
<b>Body Inside Diameter:</b>	0.6250 Inches Minimum And 0.6265 Inches Maximum
<b>Corner Shape:</b>	Chamfered Inside Right Corner
<b>Corner Shape:</b>	Chamfered Inside Left Corner
<b>Corner Shape:</b>	Square Outside Left Corner
<b>Corner Shape:</b>	Square Outside Right Corner
<b>Surface Finish:</b>	125.0 Microinches Intermediate Layer
<b>Special Features:</b>	Id And Od To Be Parallel And Concentric Within 0.0030 Tir
<b>Material:</b>	Steel Comp 4130 Overall Or Steel Comp 8630 Overall
<b>Material Document And Classification:</b>	Mil-s-6758 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
<b>Style Designator:</b>	17c Solid, Plain, No Outside Flanges
<b>Style Designator:</b>	Solid, Plain, No Outside Flanges
<b>Specification/standard Data:</b>	80205-nas75 Professional/industrial Association Standard

## How to Order

Order this bushing from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS75-10-015> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.