

**Description**

Length: 63/64", NAS75 series bushing

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                               |
|-------------------------|-------------------------------|
| SKU / Model:            | NAS7510100                    |
| Minimum Qty (MOQ):      | 5                             |
| NSN:                    | 3120-00-126-5094              |
| ECCN:                   | EAR99                         |
| National Motor Freight: | 114800, Bearing,roller,thrust |



\* See page 2 for technical characteristics

## P/N NAS75-10-100 Specifications

|   |  |
|---|--|
| <b>Overall Length:</b>                                | 0.9950 Inches Minimum And 1.0000 Inches Maximum  |
| <b>Body Outside Diameter:</b>                         | 0.8132 Inches Minimum And 0.8142 Inches Maximum  |
| <b>Body Inside Diameter:</b>                          | 0.6250 Inches Minimum And 0.6265 Inches Maximum  |
| <b>Corner Shape:</b>                                  | Chamfered Inside Right Corner  |
| <b>Corner Shape:</b>                                  | Chamfered Inside Left Corner   |
| <b>Corner Shape:</b>                                  | Square Outside Left Corner   |
| <b>Corner Shape:</b>                                  | Square Outside Right Corner  |
| <b>Surface Finish:</b>                                | 125.0 Microinches Intermediate Layer   |
| <b>Material:</b>                                      | Steel Comp 4130 Overall Or Steel Comp 8630 Overall   |
| <b>Material Document And Classification:</b>          | Mil-s-6758 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall |
| <b>Surface Treatment:</b>                             | Cadmium Overall  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall  |
| <b>Style Designator:</b>                              | 17c Solid, Plain, No Outside Flanges   |
| <b>Style Designator:</b>                              | Solid, Plain, No Outside Flanges   |
| <b>Specification/standard Data:</b>                   | 80205-nas75 Professional/industrial Association Standard   |

## How to Order

Order this sleeve bushing from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS75-10-100> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.