

## P/N NAS75-3-004

### **Description**

for bolt size: #10 length: 1/8", cadmium plated alloy steel

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS753004

Minimum Qty (MOQ): 10

NSN: 3120-00-516-1808

ECCN: EAR99

National Motor Freight: 114850, Bearing / Bushing O / T Ball / Roller I / S









<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS75-3-004 Specifications

Overall Length:	0.1200 Inches Minimum And 0.1250 Inches Maximum
Body Outside Diameter:	0.3131 Inches Minimum And 0.3136 Inches Maximum
Body Inside Diameter:	0.1900 Inches Minimum And 0.1915 Inches Maximum
Corner Shape:	Chamfered Inside Right Corner
Corner Shape:	Chamfered Inside Left Corner
Corner Shape:	Square Outside Left Corner
Corner Shape:	Square Outside Right Corner
Surface Finish:	125.0 Microinches Intermediate Layer
Special Features:	Id And Od To Be Parallel And Concentric Within 0.0030 Tir
Material:	Steel Comp 4130 Overall Or Steel Comp 8630 Overall
Material Document And Classification:	Mil-s-6758 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Style Designator:	17c Solid, Plain, No Outside Flanges
Style Designator:	Solid, Plain, No Outside Flanges
Specification/standard Data:	80205-nas75 Professional/industrial Association Standard

## **How to Order**

Order this sleeve bushing from our inventory online by visiting <a href="https://military-fasteners.com/bushings/sleeve+bushings/NAS75-3-004">https://military-fasteners.com/bushings/sleeve+bushings/NAS75-3-004</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.