

P/N NAS75-3-006

Description

for bolt size: #10 length: 3/16", cadmium plated alloy steel

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS753006

Minimum Qty (MOQ): 10

NSN: 3120-00-516-1860

ECCN: EAR99

National Motor Freight: 114850, Bearing / Bushing O / T Ball / Roller I / S









P/N NAS75-3-006 Specifications

Overall Length:0.1825 Inches Minimum And 0.1875 Inches MaximumBody Outside Diameter:0.3131 Inches Minimum And 0.3136 Inches MaximumBody Inside Diameter:0.1900 Inches Minimum And 0.1915 Inches MaximumCorner Shape:Chamfered Inside Right CornerCorner Shape:Chamfered Inside Left Corner
Body Inside Diameter: 0.1900 Inches Minimum And 0.1915 Inches Maximum Corner Shape: Chamfered Inside Right Corner
Corner Shape: Chamfered Inside Right Corner
Corner Shape: Chamfered Inside Left Corner
Corner Shape: Square Outside Left Corner
Corner Shape: Square Outside Right Corner
Surface Finish: 125.0 Microinches Intermediate Layer
Special Features: Id And Od To Be Parallel And Concentric Within 0.0030 Tir
Material: Steel Comp 4130 Overall Or Steel Comp 8630 Overall
Material Document And Classification: Mil-s-6758 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall
Surface Treatment: Cadmium Overall
Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Style Designator: 17c Solid, Plain, No Outside Flanges
Style Designator: Solid, Plain, No Outside Flanges
Specification/standard Data: 80205-nas75 Professional/industrial Association Standard

How to Order

Order this sleeve bushing from our inventory online by visiting https://military-fasteners.com/bushings/sleeve+bushings/NAS75-3-006 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.