

## P/N NAS75-3-007

### **Description**

for bolt size: #10 length: 7/32", cadmium plated alloy steel

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS753007

Minimum Qty (MOQ): 10

NSN: 3120-00-288-2368

National Motor Freight: 114850, Bearing / Bushing O / T Ball / Roller I / S



<sup>\*</sup> See page 2 for technical characteristics

# **P/N NAS75-3-007 Specifications**

Overall Length:	0.2137 Inches Minimum And 0.2187 Inches Maximum
Body Outside Diameter:	0.3131 Inches Minimum And 0.3136 Inches Maximum
Body Inside Diameter:	0.1900 Inches Minimum And 0.1915 Inches Maximum
Corner Shape:	Chamfered Inside Right Corner
Corner Shape:	Chamfered Inside Left Corner
Corner Shape:	Square Outside Left Corner
Corner Shape:	Square Outside Right Corner
Surface Finish:	125.0 Microinches Overall
Material:	Steel Comp 8630 Overall
Material Document And Classification:	Mil-s-6050,comp 8630 Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Style Designator:	17c Solid, Plain, No Outside Flanges
Style Designator:	Solid, Plain, No Outside Flanges

# **How to Order**

Order this sleeve bushing from our inventory online by visiting <a href="https://military-fasteners.com/bushings/sleeve+bushings/NAS75-3-007">https://military-fasteners.com/bushings/sleeve+bushings/NAS75-3-007</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bushings/sleeve+bushings/NAS75-3-007">https://military-fasteners.com/bushings/sleeve+bushings/NAS75-3-007</a> and selecting the quantity you