

P/N NAS75-3-009

Military-Fasteners.com

Description

for bolt size: #10 length: 9/32", cadmium plated alloy steel, NAS75 series bushing

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	NAS753009
Minimum Qty (MOQ):	10
NSN:	3120-00-288-2332
Schedule B:	8483.30.8090
ECCN:	EAR99
National Motor Freight:	114850, Bearing / Bushing O / T Ball / Roller I / S



P/N NAS75-3-009 Specifications

Overall Length:	0.2762 Inches Minimum And 0.2812 Inches Maximum
Body Outside Diameter:	0.3131 Inches Minimum And 0.3136 Inches Maximum
Body Inside Diameter:	0.1900 Inches Minimum And 0.1915 Inches Maximum
Corner Shape:	Chamfered Inside Right Corner
Corner Shape:	Chamfered Inside Left Corner
Corner Shape:	Square Outside Left Corner
Corner Shape:	Square Outside Right Corner
Surface Finish:	125.0 Microinches Intermediate Layer
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Style Designator:	17c Solid, Plain, No Outside Flanges
Style Designator:	Solid, Plain, No Outside Flanges
Specification/standard Data:	80205-nas75 Professional/industrial Association Standard

How to Order

Order this sleeve bushing from our inventory online by visiting <u>https://military-fasteners.com/bushings/sleeve+bushings/NAS75-3-009</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.