

P/N NAS75-4-005

Description

size: 1/4", length: 5/32", cadmium plated alloy steel

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS754005

Minimum Qty (MOQ): 10


NSN: 3120-00-287-6988

ECCN: EAR99

National Motor Freight: 114850, Bearing / Bushing O / T Ball / Roller I / S







^{*} See page 2 for technical characteristics

P/N NAS75-4-005 Specifications

Overall Length:	0.1512 Inches Minimum And 0.1562 Inches Maximum
Body Outside Diameter:	0.3756 Inches Minimum And 0.3761 Inches Maximum
Body Inside Diameter:	0.2500 Inches Minimum And 0.2515 Inches Maximum
Corner Shape:	Chamfered Inside Right Corner
Corner Shape:	Chamfered Inside Left Corner
Corner Shape:	Square Outside Left Corner
Corner Shape:	Square Outside Right Corner
Surface Finish:	125.0 Microinches Intermediate Layer
Special Features:	Id And Od To Be Parallel And Concentric Within 0.0030 Tir
Material:	Steel Comp 4130 Overall Or Steel Comp 8630 Overall
Material Document And Classification:	Mil-s-6758 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Style Designator:	17c Solid, Plain, No Outside Flanges
Style Designator:	Solid, Plain, No Outside Flanges
Specification/standard Data:	80205-nas75 Professional/industrial Association Standard

How to Order

Order this sleeve bushing from our inventory online by visiting https://military-fasteners.com/bushings/sleeve+bushings/NAS75-4-005 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.