# P/N NAS75-5-004

## Description

for bolt size: 5/16" length: 1/8", cadmium plated alloy steel

\* Manufacturer certifications are shipped with your order FREE of charge

**Order this part online**

## Additional Information

| SKU / Model: | NAS755004 |
|---|---|
| Minimum Qty (MOQ): | 5 |
| NSN: | 3120-00-836-2585 |
| National Motor Freight: | 114850, Bearing / Bushing O / T Ball / Roller I / S |

NO IMAGE AVAILABLE

\* See page 2 for technical characteristics

# P/N NAS75-5-004 Specifications

| | |
|---|---|
| **Overall Length:** | 0.1200 Inches Minimum And 0.1250 Inches Maximum |
| **Body Outside Diameter:** | 0.4381 Inches Minimum And 0.4386 Inches Maximum |
| **Body Inside Diameter:** | 0.3125 Inches Minimum And 0.3140 Inches Maximum |
| **Corner Shape:** | Chamfered Inside Right Corner |
| **Corner Shape:** | Chamfered Inside Left Corner |
| **Corner Shape:** | Square Outside Left Corner |
| **Corner Shape:** | Square Outside Right Corner |
| **Surface Finish:** | 125.0 Microinches Intermediate Layer |
| **Special Features:** | Id And Od To Be Parallel And Concentric Within 0.0030 Tir |
| **Material:** | Steel Comp 4130 Overall Or Steel Comp 8630 Overall |
| **Material Document And Classification:** | Mil-s-6758 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall |
| **Surface Treatment:** | Cadmium Overall |
| **Surface Treatment Document And Classification:** | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall |
| **Style Designator:** | 17c Solid, Plain, No Outside Flanges |
| **Specification/standard Data:** | 80205-nas75 Professional/industrial Association Standard |

# How to Order

Order this sleeve bushing from our inventory online by visiting https://military-fasteners.com/bushings/sleeve+bushings/NAS75-5-004 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.