

Description

for bolt size: 5/16" length: 7/32", cadmium plated alloy steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS755007
Minimum Qty (MOQ):	5
NSN:	3120-00-661-7406
ECCN:	EAR99
National Motor Freight:	115620, Bushings Noi I / S

NO IMAGE
AVAILABLE

P/N NAS75-5-007 Specifications

Overall Length:	0.2138 Inches Minimum And 0.2188 Inches Maximum
Body Outside Diameter:	0.4381 Inches Minimum And 0.4386 Inches Maximum
Body Inside Diameter:	0.3125 Inches Minimum And 0.3140 Inches Maximum
Corner Shape:	Chamfered Inside Right Corner
Corner Shape:	Chamfered Inside Left Corner
Corner Shape:	Square Outside Left Corner
Corner Shape:	Square Outside Right Corner
Surface Finish:	125.0 Microinches Intermediate Layer
Special Features:	Id And Od To Be Parallel And Concentric Within 0.0030 Tir
Material:	Steel Comp 4130 Overall Or Steel Comp 8630 Overall
Material Document And Classification:	Mil-s-6758 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Style Designator:	17c Solid, Plain, No Outside Flanges
Style Designator:	Solid, Plain, No Outside Flanges
Specification/standard Data:	80205-nas75 Professional/industrial Association Standard

How to Order

Order this sleeve bushing from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS75-5-007> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.