

# **P/N NAS75-6-012**

## **Description**

NAS75-6-012 Sleeve Bushing

\* Manufacturer certifications are shipped with your order FREE of charge

# Order this part online

#### **Additional Information**

SKU / Model:	NAS756012
Minimum Qty (MOQ):	5
NSN:	3120-00-661-7358
ECCN:	EAR99
National Motor Freight:	115620, Bushings Noi I / S



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS75-6-012 Specifications

0.3700 Inches Minimum And 0.3750 Inches Maximum
0.5006 Inches Minimum And 0.5013 Inches Maximum
0.3750 Inches Minimum And 0.3765 Inches Maximum
Chamfered Inside Right Corner
Chamfered Inside Left Corner
Square Outside Left Corner
Square Outside Right Corner
125.0 Microinches Intermediate Layer
Steel Comp 8630 Overall Or Steel Comp 4130 Overall
Mil-s-6050 Mil Spec 1st Material Response Overall Or Mil-s-6758 Mil Spec 2nd Material Response Overall
Cadmium Overall
Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
17c Solid, Plain, No Outside Flanges
Solid, Plain, No Outside Flanges
80205-nas75 Professional/industrial Association Standard

### **How to Order**

Order this sleeve bushing from our inventory online by visiting <a href="https://military-fasteners.com/bushings/sleeve+bushings/NAS75-6-012">https://military-fasteners.com/bushings/sleeve+bushings/NAS75-6-012</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bushings/sleeve+bushings/NAS75-6-012">https://military-fasteners.com/bushings/sleeve+bushings/NAS75-6-012</a> and selecting the quantity you