

Description

NAS75-6-019 Sleeve Bushing

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS756019
Minimum Qty (MOQ):	10
NSN:	3120-00-671-7174
Schedule B:	8482.99.7060
ECCN:	EAR99
National Motor Freight:	114850, Bearing / Bushing O / T Ball / Roller I / S



\* See page 2 for technical characteristics

## P/N NAS75-6-019 Specifications

<b>Overall Length:</b>	0.5887 Inches Minimum And 0.5937 Inches Maximum
<b>Body Outside Diameter:</b>	0.5006 Inches Minimum And 0.5013 Inches Maximum
<b>Body Inside Diameter:</b>	0.3750 Inches Minimum And 0.3765 Inches Maximum
<b>Corner Shape:</b>	Chamfered Inside Right Corner
<b>Corner Shape:</b>	Chamfered Inside Left Corner
<b>Corner Shape:</b>	Square Outside Left Corner
<b>Corner Shape:</b>	Square Outside Right Corner
<b>Surface Finish:</b>	125.0 Microinches Intermediate Layer
<b>Material:</b>	Steel Comp 8630 Overall Or Steel Comp 4130 Overall
<b>Material Document And Classification:</b>	Mil-s-6050 Mil Spec 1st Material Response Overall Or Mil-s-6758 Mil Spec 2nd Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
<b>Style Designator:</b>	17c Solid, Plain, No Outside Flanges
<b>Style Designator:</b>	Solid, Plain, No Outside Flanges
<b>Specification/standard Data:</b>	80205-nas75 Professional/industrial Association Standard

## How to Order

Order this sleeve bushing from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS75-6-019> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.