

P/N NAS7502-2

Description

length: 0.448", grip: 0.125", thread: 8-32, 100°, close tolerance bolt - cadmium plated steel

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	NAS75022
Minimum Qty (MOQ):	50
NSN:	5305-01-493-9051



P/N NAS7502-2 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.323 Inches Nominal
Fastener Length:	0.448 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.331 Inches Maximum
Grip Diameter:	0.1625 Inches Minimum And 0.1635 Inches Maximum
Internal Drive Style:	Cross Recess Type Iii
Nominal Thread Diameter:	0.164 Inches
Grip Length:	0.376 Inches Nominal
Thread Quantity Per Inch:	32
Countersink Angle:	100.0 Degrees Nominal
Material:	Steel Corrosion Resisting Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unjf

How to Order

Order this close tolerance screw from our inventory online by visiting https://military-fasteners.com/screws/close+tolerance+screws/NAS7502-2 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/close+tolerance+screws/NAS7502-2 and selecting the