

Description

NAS7502U1 Close Tolerance Screw

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS7502U1
Minimum Qty (MOQ):	10
NSN:	5305-01-444-0025
Schedule B:	7318.15.2091
ECCN:	EAR99
National Motor Freight:	093490, Bolt / Nut / Screw / Clips / Fastener / Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS7502U1 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.323 Inches Nominal
Fastener Length:	0.948 Inches Nominal
Head Style:	Round Wedge
Head Diameter:	0.296 Inches Minimum And 0.331 Inches Maximum
Head Height:	0.072 Inches Maximum
Grip Diameter:	0.1630 Inches Minimum And 0.1635 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Grip Length:	0.625 Inches Nominal
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Nas4003 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjc

How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS7502U1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.