

**Description**

NAS7502U1 Close Tolerance Screw

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS7502U1
Minimum Qty (MOQ):	10
NSN:	5305-01-444-0025
Schedule B:	7318.15.2091
ECCN:	EAR99
National Motor Freight:	093490, Bolt / Nut / Screw / Clips / Fastener / Etc

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS7502U1 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.323 Inches Nominal
<b>Fastener Length:</b>	0.948 Inches Nominal
<b>Head Style:</b>	Round Wedge
<b>Head Diameter:</b>	0.296 Inches Minimum And 0.331 Inches Maximum
<b>Head Height:</b>	0.072 Inches Maximum
<b>Grip Diameter:</b>	0.1630 Inches Minimum And 0.1635 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.164 Inches
<b>Grip Length:</b>	0.625 Inches Nominal
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Nas4003 Assn Std Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjc

## How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS7502U1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.