

Description

length: 0.448", grip: 0.125", thread: 8-32, 100°, close tolerance bolt - unplated steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-------------------------------|
| SKU / Model: | NAS7502U2 |
| Minimum Qty (MOQ): | 50 |
| NSN: | 5305-01-617-7017 |
| National Motor Freight: | 096640, Screws, Iron Or Steel |

NO IMAGE
AVAILABLE

P/N NAS7502U2 Specifications

| | |
|----------------------------------|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.323 Inches Nominal |
| Fastener Length: | 0.423 Inches Minimum And 0.463 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.296 Inches Minimum And 0.331 Inches Maximum |
| Grip Diameter: | 0.163 Inches Nominal |
| Internal Drive Style: | Cross Recess Type Iii |
| Nominal Thread Diameter: | 0.164 Inches |
| Grip Length: | 0.115 Inches Minimum And 0.135 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Material: | Iron Alloy 660 Overall |
| Thread Series Designator: | Unjc |

How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS7502U2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.