

Description

length: 0.448", grip: 0.125", thread: 8-32, 100°, close tolerance bolt - unplated steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS7502U2
Minimum Qty (MOQ):	50
NSN:	5305-01-617-7017
National Motor Freight:	096640, Screws, Iron Or Steel



P/N NAS7502U2 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.323 Inches Nominal
Fastener Length:	0.423 Inches Minimum And 0.463 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.296 Inches Minimum And 0.331 Inches Maximum
Grip Diameter:	0.163 Inches Nominal
Internal Drive Style:	Cross Recess Type Iii
Nominal Thread Diameter:	0.164 Inches
Grip Length:	0.115 Inches Minimum And 0.135 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Iron Alloy 660 Overall
Thread Series Designator:	Unjc

How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS7502U2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.