

Description


length: 0.511", grip: 0.188", thread: 8-32, close tolerance, unplated steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS7502U3
Minimum Qty (MOQ):	25
NSN:	5305-01-485-5995
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS7502U3 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.323 Inches Nominal
Fastener Length:	0.424 Inches Minimum And 0.454 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.331 Inches Maximum
Head Height:	0.072 Inches Nominal
Internal Drive Style:	Cross Recess Type Iii
End Item Identification:	1055014504243
Nominal Thread Diameter:	0.1640 Inches
Thread Quantity Per Inch:	32
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Corrosion Resisting
Thread Series Designator:	Unjc

How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS7502U3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.