

**Description**

length: 0.511", grip: 0.188", thread: 8-32, close tolerance, unplated steel

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS7502U3
Minimum Qty (MOQ):	25
NSN:	5305-01-485-5995
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N NAS7502U3 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.323 Inches Nominal
<b>Fastener Length:</b>	0.424 Inches Minimum And 0.454 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.331 Inches Maximum
<b>Head Height:</b>	0.072 Inches Nominal
<b>Internal Drive Style:</b>	Cross Recess Type Iii
<b>End Item Identification:</b>	1055014504243
<b>Nominal Thread Diameter:</b>	0.1640 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Screw Material:</b>	Steel Corrosion Resisting
<b>Thread Series Designator:</b>	Unjc

## How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS7502U3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.