

Description

Thread Qty: 32, Material: Iron, Surface Treatment: Cadmium and Chromate, Head Style: Flat Countersunk NAS7503-10 Screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS750310 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5305-01-339-0224 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N NAS7503-10 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.323 Inches Nominal |
| Fastener Length: | 0.933 Inches Minimum And 0.963 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.338 Inches Minimum And 0.381 Inches Maximum |
| Grip Diameter: | 0.1885 Inches Minimum And 0.1895 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.190 Inches |
| Grip Length: | 0.615 Inches Minimum And 0.635 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas7503 Professional/industrial Association Standard |

How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS7503-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.