

Description

Thread Qty: 32, Material: Iron, Surface Treatment: Cadmium, Tensile Strength: 160000, Head Style: Flat Countersunk NAS7503-6 Screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS75036
Minimum Qty (MOQ):	10
NSN:	5306-01-521-2052
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N NAS7503-6 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.323 Inches Nominal
Fastener Length:	0.698 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.338 Inches Minimum And 0.381 Inches Maximum
Grip Diameter:	0.188 Inches Minimum And 0.189 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.375 Inches Nominal
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5853 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416, Tyii, Cl2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas7503 Professional/industrial Association Standard

How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS7503-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.