

Description

Length: 3/32

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---------------------------------|
| SKU / Model: | NAS76A3003 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 3120-00-288-2799 |
| ECCN: | EAR99 |
| National Motor Freight: | 114870, Bearing / Bushing Metal |



* See page 2 for technical characteristics

P/N NAS76A3-003 Specifications

| | |
|---|--|
| Overall Length: | 0.0937 Inches Nominal |
| Body Outside Diameter: | 0.3131 Inches Minimum And 0.3136 Inches Maximum |
| Body Inside Diameter: | 0.1900 Inches Minimum And 0.1915 Inches Maximum |
| Corner Shape: | Square All Corners |
| Surface Finish: | 125.0 Microinches Intermediate Layer |
| Material: | Copper Alloy 630 Overall |
| Material Document And Classification: | Qq-b-679 Fed Spec Single Material Response Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416 Type 2,class 3 Fed Spec All Treatment Responses Overall |
| Style Designator: | 17c Solid, Plain, No Outside Flanges |
| Style Designator: | Solid, Plain, No Outside Flanges |
| Specification/standard Data: | 80205-nas76 Professional/industrial Association Standard |

How to Order

Order this sleeve bushing from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS76A3-003> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.