

Description

Length: 3/32

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS76A3003
Minimum Qty (MOQ):	10
NSN:	3120-00-288-2799
ECCN:	EAR99
National Motor Freight:	114870, Bearing / Bushing Metal

NO IMAGE
AVAILABLE

P/N NAS76A3-003 Specifications

Overall Length:	0.0937 Inches Nominal
Body Outside Diameter:	0.3131 Inches Minimum And 0.3136 Inches Maximum
Body Inside Diameter:	0.1900 Inches Minimum And 0.1915 Inches Maximum
Corner Shape:	Square All Corners
Surface Finish:	125.0 Microinches Intermediate Layer
Material:	Copper Alloy 630 Overall
Material Document And Classification:	Qq-b-679 Fed Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Type 2,class 3 Fed Spec All Treatment Responses Overall
Style Designator:	17c Solid, Plain, No Outside Flanges
Style Designator:	Solid, Plain, No Outside Flanges
Specification/standard Data:	80205-nas76 Professional/industrial Association Standard

How to Order

Order this sleeve bushing from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS76A3-003> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.