

## P/N NAS76A3-005P

### **Description**

Length: 5/32"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS76A3005P

Minimum Qty (MOQ): 10 EA

NSN: 3120-00-287-8580

National Motor Freight: 114870, Bearing / Bushing Metal



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS76A3-005P Specifications

0.1512 Inches Minimum And 0.1562 Inches Maximum
0.3131 Inches Minimum And 0.3136 Inches Maximum
0.1900 Inches Minimum And 0.1915 Inches Maximum
Chamfered Inside Right Corner
Chamfered Inside Left Corner
Square Outside Left Corner
Square Outside Right Corner
125.0 Microinches Intermediate Layer
Copper Alloy 642 Overall
Qq-c-465 Fed Spec Single Material Response Overall
Cadmium Overall
Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
17c Solid, Plain, No Outside Flanges
Solid, Plain, No Outside Flanges
80205-nas76 Professional/industrial Association Standard

## **How to Order**

Order this bushing from our inventory online by visiting <a href="https://military-fasteners.com/bushings/sleeve+bushings/NAS76A3-005P">https://military-fasteners.com/bushings/sleeve+bushings/NAS76A3-005P</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bushings/NAS76A3-005P">https://military-fasteners.com/bushings/sleeve+bushings/NAS76A3-005P</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bushings/NAS76A3-005P">https://military-fasteners.com/bushings/sleeve+bushings/NAS76A3-005P</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bushings/NAS76A3-005P">https://military-fasteners.com/bushings/NAS76A3-005P</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bushings/NAS76A3-005P">https://military-fasteners.com/bushings/NAS76A3-005P</a> and selecting the property of the property of