

Description

Length: 3/16",

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS76A3006
Minimum Qty (MOQ):	10
NSN:	3120-00-517-8451
ECCN:	EAR99
National Motor Freight:	114870, Bearing / Bushing Metal



NO IMAGE
AVAILABLE

P/N NAS76A3-006 Specifications

Overall Length:	0.1825 Inches Minimum And 0.1875 Inches Maximum
Body Outside Diameter:	0.3131 Inches Minimum And 0.3141 Inches Maximum
Body Inside Diameter:	0.1900 Inches Minimum And 0.1915 Inches Maximum
Corner Shape:	Chamfered Inside Right Corner
Corner Shape:	Chamfered Inside Left Corner
Corner Shape:	Square Outside Left Corner
Corner Shape:	Square Outside Right Corner
Surface Finish:	125.0 Microinches Intermediate Layer
Material:	Copper Alloy 642 Overall
Material Document And Classification:	Qq-c-465 Fed Spec Single Material Response Overall
Style Designator:	17c Solid, Plain, No Outside Flanges
Style Designator:	Solid, Plain, No Outside Flanges
Specification/standard Data:	80205-nas76 Professional/Industrial Association Standard

How to Order

Order this sleeve bushing from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS76A3-006> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.