

## P/N NAS76A3-008

## **Description**

Length: 1/4

\* Manufacturer certifications are shipped with your order EREE of charge

## Order this part online

#### **Additional Information**


SKU / Model: NAS76A3008

Minimum Qty (MOQ): 10

NSN: 3120-00-807-6200

ECCN: EAR99

National Motor Freight: 114870, Bearing / Bushing Metal











<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS76A3-008 Specifications

Overall Length:	0.2450 Inches Minimum And 0.2500 Inches Maximum
Body Outside Diameter:	0.3131 Inches Minimum And 0.3136 Inches Maximum
Body Inside Diameter:	0.1900 Inches Minimum And 0.1915 Inches Maximum
Corner Shape:	Chamfered Inside Right Corner
Corner Shape:	Chamfered Inside Left Corner
Corner Shape:	Square Outside Left Corner
Corner Shape:	Square Outside Right Corner
Surface Finish:	125.0 Microinches Intermediate Layer
Special Features:	Id And Od To Be Parallel And Concentric Within 0.0030 Tir
Material:	Copper Alloy 630 Overall
Material Document And Classification:	Mil-b-6946 Mil Spec Single Material Response Overall
Style Designator:	17c Solid, Plain, No Outside Flanges
Specification/standard Data:	80205-nas76 Professional/industrial Association Standard

### **How to Order**

Order this sleeve bushing from our inventory online by visiting <a href="https://military-fasteners.com/bushings/sleeve+bushings/NAS76A3-008">https://military-fasteners.com/bushings/sleeve+bushings/NAS76A3-008</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bushings/NAS76A3-008">https://military-fasteners.com/bushings/sleeve+bushings/NAS76A3-008</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bushings/sleeve+bushings/NAS76A3-008">https://military-fasteners.com/bushings/sleeve+bushings/NAS76A3-008</a> and selecting the quantity