

Description

Length: 21/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|----------------------------|
| SKU / Model: | NAS76A3021 |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 3120-00-517-8628 |
| National Motor Freight: | 115620, Bushings Noi I / S |



* See page 2 for technical characteristics

P/N NAS76A3-021 Specifications

| | |
|--|--|
| Overall Length: | 0.6510 Inches Minimum And 0.6560 Inches Maximum |
| Body Outside Diameter: | 0.3131 Inches Minimum And 0.3136 Inches Maximum |
| Body Inside Diameter: | 0.1900 Inches Minimum And 0.1915 Inches Maximum |
| Corner Shape: | Chamfered Inside Right Corner |
| Corner Shape: | Chamfered Inside Left Corner |
| Corner Shape: | Square Outside Left Corner |
| Corner Shape: | Square Outside Right Corner |
| Surface Finish: | 125.0 Microinches Intermediate Layer |
| Material: | Copper Alloy 642 Overall |
| Material Document And Classification: | Qq-c-465 Fed Spec Single Material Response Overall |
| Style Designator: | 17c Solid, Plain, No Outside Flanges |
| Style Designator: | Solid, Plain, No Outside Flanges |
| Specification/standard Data: | 80205-nas76 Professional/industrial Association Standard |

How to Order

Order this bushing from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS76A3-021> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.