

Description

Length: 1-9/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---------------------------------|
| SKU / Model: | NAS76A3118 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 3120-01-290-1692 |
| National Motor Freight: | 114870, Bearing / Bushing Metal |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS76A3-118 Specifications

| | |
|--|--|
| Overall Length: | 1.5575 Inches Minimum And 1.5625 Inches Maximum |
| Body Outside Diameter: | 0.3131 Inches Minimum And 0.3136 Inches Maximum |
| Body Inside Diameter: | 0.1900 Inches Minimum And 0.1915 Inches Maximum |
| Corner Shape: | Chamfered Inside Right Corner |
| Corner Shape: | Chamfered Inside Left Corner |
| Corner Shape: | Square Outside Left Corner |
| Corner Shape: | Square Outside Right Corner |
| Material: | Copper Alloy 642 Overall Or Copper Alloy 630 Overall |
| Material Document And Classification: | Qq-c-00465 Fed Spec 1st Material Response Overall Or Ams 4640 Assn Std 2nd Material Response Overall |
| Style Designator: | 17c Solid, Plain, No Outside Flanges |
| Specification/standard Data: | 80205-nas76 Professional/industrial Association Standard |

How to Order

Order this bushing from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS76A3-118> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.