

Description

Length: 3/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|-----------------------------------------------|
| SKU / Model: | NAS76A4006P |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 3120-00-720-2277 |
| National Motor Freight: | 114820, Bearings / Bushings Noi Ball / Roller |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS76A4-006P Specifications

| | |
|-------------------------------------------------------|---------------------------------------------------------------|
| Overall Length: | 0.1825 Inches Minimum And 0.1875 Inches Maximum |
| Body Outside Diameter: | 0.3756 Inches Minimum And 0.3761 Inches Maximum |
| Body Inside Diameter: | 0.2500 Inches Minimum And 0.2515 Inches Maximum |
| Corner Shape: | Chamfered Inside Right Corner |
| Corner Shape: | Chamfered Inside Left Corner |
| Corner Shape: | Square Outside Left Corner |
| Corner Shape: | Square Outside Right Corner |
| Surface Finish: | 125.0 Microinches Intermediate Layer |
| Material: | Copper Alloy 642 Overall |
| Material Document And Classification: | Qq-c-465 Fed Spec Single Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall |
| Style Designator: | 17c Solid, Plain, No Outside Flanges |
| Style Designator: | Solid, Plain, No Outside Flanges |
| Specification/standard Data: | 80205-nas76 Professional/Industrial Association Standard |

How to Order

Order this bushing from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS76A4-006P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.