

**Description**

Length: 7/32"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS76A4007P
Minimum Qty (MOQ):	15 EA
NSN:	3120-01-240-6059
National Motor Freight:	114850, Bearing / Bushing O / T Ball / Roller I / S

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS76A4-007P Specifications

<b>Overall Length:</b>	0.2137 Inches Minimum And 0.2187 Inches Maximum
<b>Body Outside Diameter:</b>	0.3756 Inches Minimum And 0.3761 Inches Maximum
<b>Body Inside Diameter:</b>	0.2500 Inches Minimum And 0.2515 Inches Maximum
<b>Corner Shape:</b>	Chamfered Inside Right Corner
<b>Corner Shape:</b>	Chamfered Inside Left Corner
<b>Corner Shape:</b>	Square Outside Left Corner
<b>Corner Shape:</b>	Square Outside Right Corner
<b>Material:</b>	Copper Alloy 642 Overall Or Copper Alloy 630 Overall
<b>Material Document And Classification:</b>	Qq-c-00465 Fed Spec 1st Material Response Overall Or Ams 4640 Assn Std 2nd Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall
<b>Style Designator:</b>	17c Solid, Plain, No Outside Flanges
<b>Specification/standard Data:</b>	80205-nas76 Professional/industrial Association Standard

## How to Order

Order this bushing from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS76A4-007P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.