

P/N NAS76A4-010

Military-Fasteners.com

#### Description

Length: 5/16",

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

SKU / Model:	NAS76A4010
Minimum Qty (MOQ):	5
NSN:	3120-00-840-0278
ECCN:	EAR99
National Motor Freight:	114870, Bearing / Bushing Metal



# P/N NAS76A4-010 Specifications

Our well I an other	0.2120 Jack an Minimum And 0.2125 Jack an Maximum
Overall Length:	0.3120 Inches Minimum And 0.3125 Inches Maximum
Body Outside Diameter:	0.3756 Inches Minimum And 0.3761 Inches Maximum
Body Inside Diameter:	0.2500 Inches Minimum And 0.2515 Inches Maximum
Corner Shape:	Chamfered Inside Right Corner
Corner Shape:	Chamfered Inside Left Corner
Corner Shape:	Square Outside Left Corner
Corner Shape:	Square Outside Right Corner
Surface Finish:	125.0 Microinches Intermediate Layer
Material:	Copper Alloy 642 Overall
Material Document And Classification:	Qq-c-465 Fed Spec Single Material Response Overall
Style Designator:	17c Solid, Plain, No Outside Flanges
Specification/standard Data:	80205-nas76 Professional/industrial Association Standard

## How to Order

Order this sleeve bushing from our inventory online by visiting <u>https://military-fasteners.com/bushings/sleeve+bushings/NAS76A4-010</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.